

AMENDMENT TO THE CLAIMS

Claims 1-12 (Canceled)

13. (Currently Amended) A friction management method for a support object supporting a portion of a human body having support bones, tissue around the support bones and skin on an outer side of the tissue, including selecting pressure regions of high loads when load is carried between the object and the human body supported, applying one or more selected individual patches interfaced between the object and the skin in the selected regions, each selected individual patch having defined peripheral edges to encircle an entire individual patch, the selected patches being made of material having an exposed surface of low friction surfaces within the peripheral edges, and adhesively securing a patch in each selected area to one of the object and the tissue.

14. (original) The friction management of claim 13, wherein the object comprises a shoe, and the selected regions include the metatarsal-phalangeal joint region.

15. (Previously Presented) The friction management method of claim 14, wherein the calcaneus region comprises the region supported on low friction surface patches.

16. (Original) The friction management method of claim 13, wherein the object comprises a prosthetic device having a socket for receiving a portion of a limb to be supported, and providing patches at specific high load locations between an interior surface of the socket and a supported limb.

17. (Currently Amended) A method of reducing trauma to tissue supported on an object including steps of selecting a plurality of

support regions of high load where shear load on tissue is likely to cause damage, and providing a separable, individual low friction surface patch having a peripheral edge defining the patch between each of the plurality of the regions of high load and an object supporting the tissue by adhesively securing each patch to one of the tissue and the object.

18.(Previously Presented) The method of claim 17, including a step of selecting the low friction material to have a coefficient of friction substantially equal to that of polytetrafluoroethylene.

19.(Original) The method of claim 17, wherein the selecting step includes identifying support regions where low friction surface patches are omitted.

20.(Original) The method of claim 17 including the step of providing a patch having a low coefficient of friction material exposed on oppositely facing support surfaces of the patch.

21.(previously presented) The method of claim 17 including one of the steps of adding and relocating at least one low friction surface patch after the tissue has been loaded against on the object for a period of time.

22.(currently amended) The friction management system of claim 13, wherein the patches are removably affixed to the portions of the ~~object exposed surface, the portion of the human body being supported on the exposed surface in regions other than the selected regions.~~

23. (currently amended) A method of reducing trauma to highly shear loaded tissue supported under load against exposed support

surfaces of an object only in selected region of the exposed support surface, including selecting at least one region of high load where shear load on tissue is likely to cause or has caused discomfort, and providing a plurality of low friction surface patches comprising a polytetrafluoroethylene film having a bonded stretch fabric on one side of the film such that the film moves with the stretch fabric and releasably securable to the exposed support surface, applying at least one of the patches between at least one selected region of high load and the exposed support surface of the object and conforming the stretch fabric to contours of the support surface in the at least one selected region by supporting the tissue such that only the selected region is supported on a low friction surface patch.

24.(cancelled)